

for reporting ambient air quality data and related information. The monitoring criteria pertain to the following areas:

- (1) Quality assurance procedures for monitor operation and data handling.
- (2) Methodology used in monitoring stations.
- (3) Operating schedule.
- (4) Siting parameters for instruments or instrument probes.
- (5) Minimum ambient air quality monitoring network requirements used to provide support to the State implementation plans (SIP), national air quality assessments, and policy decisions. These minimums are described as part of the network design requirements, including minimum numbers and placement of monitors of each type.
- (6) Air quality data reporting, and requirements for the daily reporting of an index of ambient air quality.
- (b) The requirements pertaining to provisions for an air quality surveillance system in the SIP are contained in this part.
- (c) This part also acts to establish a national ambient air quality monitoring network for the purpose of providing timely air quality data upon which to base national assessments and policy decisions.

#### § 58.3 Applicability.

This part applies to:

- (a) State air pollution control agencies.
- (b) Any local air pollution control agency to which the State has delegated authority to operate a portion of the State's SLAMS network.
- (c) Owners or operators of proposed sources.

### Subpart B—Monitoring Network

SOURCE: 71 FR 61298, Oct. 17, 2006, unless otherwise noted.

#### § 58.10 Annual monitoring network plan and periodic network assessment.

- (a)(1) Beginning July 1, 2007, the State, or where applicable local, agency shall adopt and submit to the Regional Administrator an annual monitoring network plan which shall pro-

vide for the establishment and maintenance of an air quality surveillance system that consists of a network of SLAMS monitoring stations including FRM, FEM, and ARM monitors that are part of SLAMS, NCore stations, STN stations, State speciation stations, SPM stations, and/or, in serious, severe and extreme ozone nonattainment areas, PAMS stations, and SPM monitoring stations. The plan shall include a statement of purposes for each monitor and evidence that siting and operation of each monitor meets the requirements of appendices A, C, D, and E of this part, where applicable. The annual monitoring network plan must be made available for public inspection for at least 30 days prior to submission to EPA.

(2) Any annual monitoring network plan that proposes SLAMS network modifications including new monitoring sites is subject to the approval of the EPA Regional Administrator, who shall provide opportunity for public comment and shall approve or disapprove the plan and schedule within 120 days. If the State or local agency has already provided a public comment opportunity on its plan and has made no changes subsequent to that comment opportunity, the Regional Administrator is not required to provide a separate opportunity for comment.

(3) The plan for establishing required NCore multipollutant stations shall be submitted to the Administrator not later than July 1, 2009. The plan shall provide for all required stations to be operational by January 1, 2011.

(b) The annual monitoring network plan must contain the following information for each existing and proposed site:

- (1) The AQS site identification number.
- (2) The location, including street address and geographical coordinates.
- (3) The sampling and analysis method(s) for each measured parameter.
- (4) The operating schedules for each monitor.
- (5) Any proposals to remove or move a monitoring station within a period of 18 months following plan submittal.
- (6) The monitoring objective and spatial scale of representativeness for